

## The Minimum $k$ -Cover Problem

Anna Gorbenko

Department of Intelligent Systems and Robotics  
Ural Federal University  
620083 Ekaterinburg, Russia  
gorbenko.ann@gmail.com

Vladimir Popov

Department of Intelligent Systems and Robotics  
Ural Federal University  
620083 Ekaterinburg, Russia  
Vladimir.Popov@usu.ru

Copyright © 2013 Anna Gorbenko and Vladimir Popov. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

### Abstract

We consider the problem of determining the minimum cardinality collection of substrings, each of given length  $k \geq 2$ , that “cover” a given string  $x$  of length  $n$ . We describe an approach to solve this problem. This approach is based on constructing an explicit reduction from the problem to the satisfiability problem.

**Keywords:** strings,  $k$ -covers, satisfiability

Different problems of finding regularities are thoroughly studied in theoretical computer science (see e.g. [1] – [6]). In particular, the minimum  $k$ -cover problem was introduced in [7].

Given a nonempty string  $x$  of length  $n$ , a set  $V = \{v_1, v_2, \dots, v_p\}$  of  $p$  substrings of  $x$ . We say that  $V$  is a cover for  $x$  if and only if every position of  $x$  lies within an occurrence of some  $v_i$ ,  $1 \leq i \leq p$ . In addition, if each string in  $V$  has length  $k$ , then  $V$  is a  $k$ -cover of  $x$ . If  $p$  is the minimum integer for which such a set  $V$  exists, then  $V$  is said to be a minimum  $k$ -cover of  $x$ .

THE MINIMUM  $k$ -COVER PROBLEM (MCP):

INSTANCE: An alphabet  $\Sigma$ , a string  $X$  over  $\Sigma$ , positive integers  $k$  and  $p$ .

QUESTION: Whether there exists a  $k$ -cover of  $X$  of cardinality  $p$ ?

The minimum  $k$ -cover problem is **NP**-complete (see [8]). Encoding problems as Boolean satisfiability and solving them with very efficient satisfiability algorithms has recently caused considerable interest (see e.g. [9] – [25]). In this paper, we consider an explicit reduction from MCP to the satisfiability problem. For simplicity, we use  $S[i]$  to denote the  $i$ th letter in sequence  $S$ , and  $S[i, j]$  to denote the substring of  $S$  consisting of the  $i$ th letter through the  $j$ th letter. Let  $\Sigma = \{a_1, a_2, \dots, a_{|\Sigma|}\}$ . Let

$$\begin{aligned}\varphi[1, i, j] &= \bigvee_{1 \leq l \leq |\Sigma|} x[i, j, l], \\ \varphi[2, i, j] &= \bigwedge_{1 \leq l[1] \leq |\Sigma|, 1 \leq l[2] \leq |\Sigma|, l[1] \neq l[2]} (\neg x[i, j, l[1]] \vee \neg x[i, j, l[2]]), \\ \varphi[i, j] &= \varphi[1, i, j] \wedge \varphi[2, i, j], \\ \varphi &= \bigwedge_{1 \leq i \leq p, 1 \leq j \leq k} \varphi[i, j], \\ \psi[i] &= \bigvee_{1 \leq j \leq |X| - k + 1} y[i, j], \\ \psi &= \bigwedge_{1 \leq i \leq p} \psi[i], \\ \rho[i] &= \bigvee_{1 \leq j \leq p, h_i \leq l \leq i, h_i = 1, \text{ if } i \leq k, h_i = i - k + 1, \text{ if } i > k} y[j, l], \\ \rho &= \bigwedge_{1 \leq i \leq |X|} \rho[i], \\ \tau[1, i] &= \bigwedge_{1 \leq j \leq |\Sigma|, X[i] = a_l, l \neq j} \neg z[i, j], \\ \tau[2] &= \bigwedge_{1 \leq i \leq |X|, X[i] = a_j} z[i, j], \\ \tau &= \tau[2] \wedge \bigwedge_{1 \leq i \leq |X|} \tau[1, i], \\ \eta &= \bigwedge_{1 \leq i \leq p, 1 \leq j \leq |X| - k + 1, 0 \leq t \leq k - 1, 1 \leq l \leq |\Sigma|} y[i, j] \rightarrow z[j + t, l] = x[i, 1 + t, l], \\ \xi &= \varphi \wedge \psi \wedge \rho \wedge \tau \wedge \eta.\end{aligned}$$

**Theorem.** Given a fixed alphabet  $\Sigma$ , a string  $X$  over  $\Sigma$ , positive integers  $k$  and  $p$ . There is a  $k$ -cover of  $X$  of cardinality  $p$  if and only if  $\xi$  is satisfiable.

**Proof.** Suppose that there is  $V = \{v_1, v_2, \dots, v_p\}$  that is a  $k$ -cover of  $X$  of cardinality  $p$ . Let  $x[i, j, l] = 1$  where  $1 \leq i \leq p$ ,  $1 \leq j \leq k$ ,  $v_i[j] = a_l$ ;  $x[i, j, l] = 0$  where  $1 \leq i \leq p$ ,  $1 \leq j \leq k$ ,  $v_i[j] \neq a_l$ ;  $y[i, j] = 1$  if and only if  $X[j, j + k - 1] = v_i$  where  $1 \leq i \leq p$ ,  $1 \leq j \leq |X| - k + 1$ ;  $z[i, j] = 1$  where  $1 \leq i \leq |X|$ ,  $1 \leq j \leq |\Sigma|$ ,  $X[i] = a_j$ ;  $z[i, j] = 0$  where  $1 \leq i \leq |X|$ ,  $1 \leq j \leq |\Sigma|$ ,  $X[i] \neq a_j$ .

Since  $V \subseteq \Sigma^k$ , for all  $i$  and  $j$  there is  $l$  such that  $x[i, j, l] = 1$ . Therefore,  $\varphi[1, i, j] = 1$ . In view of  $x[i, j, l] = 0$  where  $1 \leq i \leq p$ ,  $1 \leq j \leq k$ ,  $v_i[j] \neq a_l$ , it is clear that there is no more than one value of  $l$  such that  $x[i, j, l] = 1$ . Hence either  $x[i, j, l[1]] = 0$  or  $x[i, j, l[2]]$  for all  $i, j, l[1] \neq l[2]$ . Therefore,  $\varphi[2, i, j] = 1$ . So,  $\varphi = 1$ .

Note that  $V$  is a set of substrings of  $X$ . Since  $y[i, j] = 1$  if and only if  $X[j, j + k - 1] = v_i$ , it is easy to see that  $\psi[i] = 1$ . By definition,  $\psi[2, i] = 1$ . So,  $\psi = 1$ .

Since  $V$  is a  $k$ -cover of  $X$ ,  $X[r, r + k - 1] = v_j$  for some  $r$  and  $j$  such that  $1 \leq j \leq p$ ,  $r \leq i \leq r + k - 1$ . Therefore,  $\rho[i] = 1$ . So,  $\rho = 1$ . Since  $z[i, j] = 1$  where  $1 \leq i \leq |X|$ ,  $1 \leq j \leq |\Sigma|$ ,  $X[i] = a_j$ ;  $z[i, j] = 0$  where  $1 \leq i \leq |X|$ ,  $1 \leq j \leq |\Sigma|$ ,  $X[i] \neq a_j$ , it is easy to check that  $\tau = 1$ . Since  $V$  is a  $k$ -cover of  $X$ , it is clear that  $\eta = 1$ . Therefore,  $\xi = 1$ .

Suppose now that  $\xi = 1$ . Hence  $\xi = \varphi = \psi = \rho = \tau = \eta = 1$ . Since  $\varphi = 1$ , by definition,  $\varphi[1, i, j] = 1$ ,  $\varphi[2, i, j] = 1$ . It is easy to check that for all  $i$  and  $j$  there is only one value of  $l$  such that  $x[i, j, l] = 1$ . Let  $v_i[j] = a_l$ . Since  $\eta = 1$  and  $\tau = 1$ , it is clear that if  $y[i, j] = 1$ , then  $X[j, j + k - 1] = v_i$ . In view of  $\rho = 1$ , we obtain that  $V$  is a  $k$ -cover of  $X$ .  $\square$

In view of the theorem, we obtain an explicit reduction from MCP to PSAT.

Note that  $\alpha \rightarrow \beta \Leftrightarrow \neg\alpha \vee \beta$ ,  $\alpha = \beta \Leftrightarrow (\neg\alpha \vee \beta) \wedge (\alpha \vee \neg\beta)$ . Therefore,  $\eta \Leftrightarrow \eta'$  where

$$\eta' = \bigwedge_{1 \leq i \leq p, 1 \leq j \leq |X| - k + 1, 1 \leq t \leq k - 1, 1 \leq l \leq |\Sigma|} (\neg y[i, j] \vee \neg z[j + t, l] \vee x[i, 1 + t, l]) \wedge (\neg y[i, j] \vee z[j + t, l] \vee \neg x[i, 1 + t, l]).$$

Let  $\xi' = \varphi \wedge \psi \wedge \rho \wedge \tau \wedge \eta'$ . It is clear that  $\xi \Leftrightarrow \xi'$ . Since  $\xi'$  is a CNF, we obtain an explicit reduction from MCP to SAT.

Using standard transformations (see e.g. [26]) we can obtain an explicit transformation  $\xi'$  into  $\xi''$  such that  $\xi' \Leftrightarrow \xi''$  and  $\xi''$  is a 3-CNF. It is easy to see that  $\xi''$  gives us an explicit reduction from MCP to 3SAT.

There is a well known site on which posted solvers for SAT [27]. They are divided into two main classes: stochastic local search algorithms and algorithms improved exhaustive search. All solvers allow the conventional format for recording DIMACS boolean function in conjunctive normal form and solve the corresponding problem [28]. In addition to the solvers the site also represented a large set of test problems in the format of DIMACS. This set includes a randomly generated problems of 3SAT.

We create a generator of natural instances for LCS. Also we use test problems from [27]. We use algorithms from [27]. Also we design our own genetic algorithm for SAT which based on algorithms from [27].

We use heterogeneous cluster based on three clusters (Cluster USU, Linux, 8 calculation nodes, Intel Pentium IV 2.40GHz processors; umt, Linux, 256 calculation nodes, Xeon 3.00GHz processors; um64, Linux, 124 calculation nodes, AMD Opteron 2.6GHz bi-processors) [29].

Each test was run on a cluster of at least 100 nodes. The maximum solution time was 6 hours. The average time to find a solution was 11.4 minutes. The best time was 7 seconds.

**ACKNOWLEDGEMENTS.** The work was partially supported by Analytical Departmental Program “Developing the scientific potential of high school” 8.1616.2011.

## References

- [1] V. Yu. Popov, Computational complexity of problems related to DNA sequencing by hybridization, *Doklady Mathematics*, 72 (2005), 642-644.
- [2] V. Popov, The approximate period problem for DNA alphabet, *Theoretical Computer Science*, 304 (2003), 443-447.
- [3] V. Popov, The Approximate Period Problem, *IAENG International Journal of Computer Science*, 36 (2009), 268-274.
- [4] V. Popov, Approximate Periods of Strings for Absolute Distances, *Applied Mathematical Sciences*, 6 (2012), 6713-6717.
- [5] V. Popov, Multiple genome rearrangement by swaps and by element duplications, *Theoretical Computer Science*, 385 (2007), 115-126.
- [6] V. Popov, Sorting by prefix reversals, *IAENG International Journal of Applied Mathematics*, 40 (2010), 247-250.
- [7] Iliopoulos, C.S., Smyth, W.F., “On-line algorithms for k-covering,” *Proceedings of the Ninth Australasian Workshop on Combinatorial Algorithms*, Curtin University of Technology, pp. 107-116 7 /98.
- [8] Cole, R., Iliopoulos, C.S., Mohamed, M., Smyth, W.F., Yang, L., “Computing the minimum  $k$ -cover of a string,” *Proceedings of the Prague Stringology Conference*, Prague Stringology Club, pp. 51-62 9 /03.
- [9] A. Gorbenko and V. Popov, The Minimum Test Collection Problem, *Applied Mathematical Sciences*, 7 (2013), 1191-1193.
- [10] A. Gorbenko and V. Popov, The Farthest Substring Problem, *Applied Mathematical Sciences*, 7 (2013), 1209-1212.
- [11] A. Gorbenko and V. Popov, Computational Experiments for the Problem of Hamiltonian Path with Fixed Number of Color Repetitions, *Advanced Studies in Theoretical Physics*, 7 (2013), 121-126.
- [12] A. Gorbenko and V. Popov, On Hamilton Paths in Grid Graphs, *Advanced Studies in Theoretical Physics*, 7 (2013), 127-130.

- [13] A. Gorbenko and V. Popov, Computational Experiments for the Problem of Sensor-Mission Assignment in Wireless Sensor Networks, *Advanced Studies in Theoretical Physics*, 7 (2013), 135-139.
- [14] A. Gorbenko and V. Popov, The Swap Common Superstring Problem, *Applied Mathematical Sciences*, 7 (2013), 609-614.
- [15] A. Gorbenko and V. Popov, The String Barcoding Problem, *Applied Mathematical Sciences*, 7 (2013), 615-622.
- [16] A. Gorbenko and V. Popov, On Multiple Occurrences Shortest Common Superstring Problem, *Applied Mathematical Sciences*, 7 (2013), 641-644.
- [17] A. Gorbenko and V. Popov, Longest Common Parameterized Subsequences with Fixed Common Substring, *Applied Mathematical Sciences*, 7 (2013), 645-650.
- [18] A. Gorbenko and V. Popov, The Hamiltonian Alternating Path Problem, *IAENG International Journal of Applied Mathematics*, 42 (2012), 204-213.
- [19] A. Gorbenko and V. Popov, The Problem of Finding Two Edge-Disjoint Hamiltonian Cycles, *Applied Mathematical Sciences*, 6 (2012), 6563-6566.
- [20] A. Gorbenko and V. Popov, Multiple Occurrences Shortest Common Superstring Problem, *Applied Mathematical Sciences*, 6 (2012), 6573-6576.
- [21] A. Gorbenko and V. Popov, The Far From Most String Problem, *Applied Mathematical Sciences*, 6 (2012), 6719-6724.
- [22] A. Gorbenko and V. Popov, Hamiltonian Alternating Cycles with Fixed Number of Color Appearances, *Applied Mathematical Sciences*, 6 (2012), 6729-6731.
- [23] A. Gorbenko and V. Popov, On the Longest Common Subsequence Problem, *Applied Mathematical Sciences*, 6 (2012), 5781-5787.
- [24] A. Gorbenko and V. Popov, The Longest Common Parameterized Subsequence Problem, *Applied Mathematical Sciences* 6 (2012), 2851-2855.
- [25] A. Gorbenko and V. Popov, The set of parameterized  $k$ -covers problem, *Theoretical Computer Science*, 423 (2012), 19-24.
- [26] A. Gorbenko and V. Popov, The  $c$ -Fragment Longest Arc-Preserving Common Subsequence Problem, *IAENG International Journal of Computer Science*, 39 (2012), 231-238.

- [27] <http://people.cs.ubc.ca/~hoos/SATLIB/index-ubc.html>
- [28] <http://www.cs.ubc.ca/~hoos/SATLIB/Benchmarks/SAT/satformat.ps>
- [29] [http://parallel.imm.uran.ru/mvc\\_now/hardware/supercomp.htm](http://parallel.imm.uran.ru/mvc_now/hardware/supercomp.htm)

**Received: February 12, 2013**